

80mm AC FAN

CE RS

● **General Specifications**

- ⊙ Material ----- Frame:Aluminum
Impeller:Plastics (Flammability:UL94V-0 rating)
- ⊙ Dielectric Strength ----- 50/60Hz 1500VAC 1minute
- ⊙ Life time -----15000 Hours Sleeve bearing
30000 Hours Ball bearing
- ⊙ Storage Temperatur--- -30℃ ~ +70℃ (Non-condensing)
- ⊙ Bearing Type----- Ball Bearings Sleeve
- ⊙ Speed Range----- ±10%
- ⊙ Part Numbering System



SFD-AC8038H 220 B - 1

Waterproof level: 1=IP55, 2=IP68

Bearing: S=sleeve bearing, B=ball bearing

AC Voltage: 110=100-125V、220=220-240V

80 X 80 X 38mm (Mass: 366g)

Model No.	Voltage (v)	Frequency (HZ)	Rated Current (AMP)	Rated Input (Watt)	Speed (R.P.M)	Maximum Air Flow		Max.Static Pressure		Noise (dB-A)
	VAC					M3/min	CFM	mmH2O	IN H2O	
SFD-AC8038L110B	100~125	50 /60	0.09/0.10	9/10	1650/1850	0.48/0.52	17/18	2.72/2.9	0.106/0.104	17/19
SFD-AC8038L220B	220~240		0.07/0.08	9/10	1650/1850	0.48/0.52	17/18	2.72/2.9	0.106/0.104	17/19
SFD-AC8038M110B	100~125		0.11/0.13	12/14	2250/2450	0.63/0.66	22.4/23	3.15/3.65	0.124/0.143	27/31
SFD-AC8038M220B	220~240		0.08/0.09	12/14	2250/2450	0.63/0.66	22.4/23	3.15/3.65	0.124/0.143	27/31
SFD-AC8038H110B	100~125		0.13/0.15	14/16	2450/1950	0.69/0.89	24.2/31	3.35/4.85	0.132/0.192	31/35
SFD-AC8038H220B	220~240		0.10/0.11	16/18	2450/1950	0.69/0.89	24.2/31	3.35/4.85	0.132/0.192	31/35

● **Dimensions(unit:mm/inch)**

● **Air Flow-Static Pressure Characteristics**

