

92mm AC FAN

CE RS

● General Specifications

- ⌚ Material ----- Frame:Aluminum
Impeller:Plastics (Flammability:UL94V-0 rating)
- ⌚ Dielectric Strength ----- 50/60Hz 1500VAC 1minute
- ⌚ Life time -----15000 Hours Sleeve bearing
30000 Hours Ball bearing
- ⌚ Storage Temperatur--- -30℃ ~ +70℃ (Non-condensing)
- ⌚ Bearing Type----- Ball Bearings Sleeve
- ⌚ Speed Range----- ±10%
- ⌚ Part Numbering System



SFD-AC9238H 220 B - 1

Waterproof level: 1=IP55, 2=IP68

Bearing: S=sleeve bearing, B=ball bearing

AC Voltage: 110=100-125V、220=220-240V

92 X 92 X 38mm (Mass:390g)

Model No.	Voltage (v)	Frequency (HZ)	Rated Current (A/MP)	Rated Input (Watt)	Speed (R.P.M)	Maximum Air Flow		Max.Static Pressure		Noise (dB-A)
	VAC					M3/min	CFM	mmH2O	IN H2O	
SFD-AC9238L110B	100~125	50 /60	0.09/0.10	9/10	1650/1800	0.66/0.68	23/24	2.7/3.0	0.105/0.118	18/20
SFD-AC9238L220B	220~240		0.07/0.08	9/10	1650/1800	0.66/0.68	23/24	2.7/3.0	0.105/0.118	18/20
SFD-AC9238M110B	100~125		0.11/0.13	12/14	2200/2400	0.79/0.90	28/32	3.52/4.21	0.136/0.165	27/31
SFD-AC9238M220B	220~240		0.08/0.09	12/14	2200/2400	0.79/0.90	28/32	3.52/4.21	0.136/0.165	27/31
SFD-AC9238H110B	100~125		0.14/0.16	14/16	2450/2900	1.22/1.43	43/50	4.5/5.52	0.177/0.217	32/36
SFD-AC9238H220B	220~240		0.11/0.12	16/18	2450/2900	1.22/1.43	43/50	4.5/5.52	0.177/0.217	32/36

● Dimensions(unit:mm/inch)

● Air Flow-Static Pressure Characteristics

